

ADDENDUM

MODEL NUMBER *RK	HEATING INPUT	MOTOR SPEED	MOTOR HP	EXTERNAL STATIC PRESSURE (INCHES OF WATER COLUMN)															
				0.1		0.2		0.3		0.4		0.5		0.6		0.7		0.8	
				CFM	Rise	CFM	Rise	CFM	Rise	CFM	Rise	CFM	Rise	CFM	Rise	CFM	Rise	CFM	Rise
060(†)-12A	60,000	HIGH* MEDIUM LOW**	1/3	1380	-	1345	-	1330	-	1260	36	1230	37	1190	38	1160	39	1120	40
				1180	38	1145	40	1130	40	1110	41	1080	42	1060	43	1040	44	1010	45
				830	55	810	56	805	56	795	57	780	58	770	59	760	60	750	60
072(†)-08A	72,000	HIGH* MEDIUM** LOW**	1/3	1380	-	1345	-	1330	-	1260	-	1230	-	1190	46	1160	47	1120	49
				1180	46	1145	47	1130	48	1110	49	1080	50	1060	51	1040	52	1010	54
				830	65	810	67	805	67	795	68	780	70	770	71	760	71	750	72
072(†)-12A	72,000	HIGH* MEDIUM LOW**	1/3	1380	-	1345	-	1330	-	1260	-	1230	-	1190	46	1160	47	1120	49
				1180	46	1145	47	1130	48	1110	49	1080	50	1060	51	1040	52	1010	54
				830	65	810	67	805	67	795	68	780	70	770	71	760	71	750	72
072(†)-16B	72,000	HIGH* MED-HIGH MED-LOW** LOW**	1/2	1850	-	1790	-	1775	-	1755	-	1735	-	1700	-	1680	-	1650	-
				1460	-	1435	38	1420	38	1400	39	1380	39	1360	40	1340	41	1320	41
				1210	45	1195	45	1180	46	1160	47	1140	48	1120	49	1110	49	1090	50
096(†)-12B	96,000	HIGH* MEDIUM** LOW	1/3	1475	49	1460	50	1445	50	1430	51	1410	51	1400	52	1380	52	1360	53
				1200	60	1195	61	1180	61	1165	62	1145	63	1140	64	1120	65	1110	65
				795	-	785	-	770	-	755	-	735	-	720	-	710	-	690	-
096(†)-16B	96,000	HIGH* MED-HIGH MED-LOW** LOW	1/2	1950	-	1890	-	1865	-	1835	-	1805	40	1770	41	1730	42	1700	43
				1600	45	1580	46	1555	47	1525	48	1495	48	1470	49	1450	50	1420	51
				1375	53	1360	53	1335	54	1305	56	1275	57	1250	58	1230	59	1200	60
120(†)-20B	120,000	HIGH* MED-HIGH MED-LOW** LOW	3/4	2440	-	2395	-	2385	-	2375	-	2360	-	2340	-	2320	-	2300	-
				1920	47	1910	47	1900	48	1890	48	1875	48	1870	48	1860	49	1840	49
				1630	56	1620	56	1610	56	1600	57	1585	57	1580	57	1570	58	1550	58
135(†)-20B	135,000	HIGH* MED-HIGH** MED-LOW LOW	3/4	2440	41	2395	42	2385	42	2375	42	2360	42	2340	43	2320	43	2300	44
				1920	51	1910	52	1900	52	1890	53	1875	53	1870	53	1860	54	1840	55
				1630	61	1620	62	1610	62	1600	63	1585	63	1580	63	1570	64	1550	65
				1430	69	1425	70	1415	70	1405	-	1390	-	1380	-	1370	-		

* FACTORY SET COOLING SPEED
**FACTORY SET HEATING SPEED
† = CAN BE EITHER "C" OR "N"

NOTES: 1. AIRFLOW RATES OF 1800 CFM OR MORE REQUIRE TWO RETURN AIR CONNECTIONS. DATA IS FOR OPERATION WITH FILTER(S)
2. TEMPERATURE RISES IN THE TABLE ARE APPROXIMATE. ACTUAL TEMPERATURE RISES MAY VARY
3. TEMPERATURE RISES DISPLAYED IN ITALICS ARE FOR REFERENCE ONLY.
4. TEMPERATURE RISES DISPLAYED IN BOLD ARE RATED TEMPERATURE RISES.

O'Fallon, MO

NORDYNE



7084830

Printed in U.S.A.

ADDENDUM

MODEL NUMBER *RK	HEATING INPUT	MOTOR SPEED	MOTOR HP	EXTERNAL STATIC PRESSURE (INCHES OF WATER COLUMN)															
				0.1		0.2		0.3		0.4		0.5		0.6		0.7		0.8	
				CFM	Rise	CFM	Rise	CFM	Rise	CFM	Rise	CFM	Rise	CFM	Rise	CFM	Rise	CFM	Rise
060(†)-12A	60,000	HIGH* MEDIUM LOW**	1/3	1380	-	1345	-	1330	-	1260	36	1230	37	1190	38	1160	39	1120	40
				1180	38	1145	40	1130	40	1110	41	1080	42	1060	43	1040	44	1010	45
				830	55	810	56	805	56	795	57	780	58	770	59	760	60	750	60
072(†)-08A	72,000	HIGH* MEDIUM** LOW**	1/3	1380	-	1345	-	1330	-	1260	-	1230	-	1190	46	1160	47	1120	49
				1180	46	1145	47	1130	48	1110	49	1080	50	1060	51	1040	52	1010	54
				830	65	810	67	805	67	795	68	780	70	770	71	760	71	750	72
072(†)-12A	72,000	HIGH* MEDIUM LOW**	1/3	1380	-	1345	-	1330	-	1260	-	1230	-	1190	46	1160	47	1120	49
				1180	46	1145	47	1130	48	1110	49	1080	50	1060	51	1040	52	1010	54
				830	65	810	67	805	67	795	68	780	70	770	71	760	71	750	72
072(†)-16B	72,000	HIGH* MED-HIGH MED-LOW** LOW**	1/2	1850	-	1790	-	1775	-	1755	-	1735	-	1700	-	1680	-	1650	-
				1460	-	1435	38	1420	38	1400	39	1380	39	1360	40	1340	41	1320	41
				1210	45	1195	45	1180	46	1160	47	1140	48	1120	49	1110	49	1090	50
096(†)-12B	96,000	HIGH* MEDIUM** LOW	1/3	1475	49	1460	50	1445	50	1430	51	1410	51	1400	52	1380	52	1360	53
				1200	60	1195	61	1180	61	1165	62	1145	63	1140	64	1120	65	1110	65
				795	-	785	-	770	-	755	-	735	-	720	-	710	-	690	-
096(†)-16B	96,000	HIGH* MED-HIGH MED-LOW** LOW	1/2	1950	-	1890	-	1865	-	1835	-	1805	40	1770	41	1730	42	1700	43
				1600	45	1580	46	1555	47	1525	48	1495	48	1470	49	1450	50	1420	51
				1375	53	1360	53	1335	54	1305	56	1275	57	1250	58	1230	59	1200	60
120(†)-20B	120,000	HIGH* MED-HIGH MED-LOW** LOW	3/4	2440	-	2395	-	2385	-	2375	-	2360	-	2340	-	2320	-	2300	-
				1920	47	1910	47	1900	48	1890	48	1875	48	1870	48	1860	49	1840	49
				1630	56	1620	56	1610	56	1600	57	1585	57	1580	57	1570	58	1550	58
135(†)-20B	135,000	HIGH* MED-HIGH** MED-LOW LOW	3/4	2440	41	2395	42	2385	42	2375	42	2360	42	2340	43	2320	43	2300	44
				1920	51	1910	52	1900	52	1890	53	1875	53	1870	53	1860	54	1840	55
				1630	61	1620	62	1610	62	1600	63	1585	63	1580	63	1570	64	1550	65
				1430	69	1425	70	1415	70	1405	-	1390	-	1380	-	1370	-		

* FACTORY SET COOLING SPEED
**FACTORY SET HEATING SPEED
† = CAN BE EITHER "C" OR "N"

NOTES: 1. AIRFLOW RATES OF 1800 CFM OR MORE REQUIRE TWO RETURN AIR CONNECTIONS. DATA IS FOR OPERATION WITH FILTER(S)
2. TEMPERATURE RISES IN THE TABLE ARE APPROXIMATE. ACTUAL TEMPERATURE RISES MAY VARY
3. TEMPERATURE RISES DISPLAYED IN ITALICS ARE FOR REFERENCE ONLY.
4. TEMPERATURE RISES DISPLAYED IN BOLD ARE RATED TEMPERATURE RISES.

O'Fallon, MO

NORDYNE



7084830

Printed in U.S.A.